

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICE

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|--------------------------------------|---|--|---|--------------------------------------|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | X | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | X | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | X | NOTICE OF INTENTION (OTHER) Dual Complete | X | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

January 24, 1955
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the R. R. Andrews

Gulf Oil Corporation
(Company or Operator) Well No. 2 in G (Unit)
SW $\frac{1}{4}$ NE $\frac{1}{4}$ of Sec. 32, T. 22-S, R. 38-E, NMPM., Drinkard Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to dually complete as Oil-Gas well in the Drinkard and Tubb Zones as follows:

1. Set cast iron bridge plug at 6850' with 2 sacks cement on top.
2. Perforate 5-1/2" casing from 6745-6795' with 4, 1/2" Jet Holes per foot.
3. Sub and test. Treat with 10,000 gallons acid if warranted.
4. Perforate 5-1/2" casing from 6080-6110' and from 6150-6250' with 4, 1/2" Hpf.
5. Sub and test. Treat perforations from 6080-6110' with 2500 gallons acid free and lower set (6150-6250') with 10,000 gallons acid free if warranted.
6. Sub and test.
7. Produce Drinkard Oil thru tubing and Tubb Gas thru 5-1/2" - 2-3/8" annulus.

DC-175.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By S. G. Stanley

Title.....

Gulf Oil Corporation

Company or Operator

By [Signature]

Position Asst. Area Supt. of Prod.

Send Communications regarding well to:

Name Gulf Oil Corporation

Address Box 2167, Hobbs, N. M.