


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	✓	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Hobbs, New Mexico

June 12, 1946

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company State "G" Well No. 2 in the  
Company or Operator Lease

NW/4 NW/4 of Sec. 32, T. 22 S, R. 38 E, N. M. P. M.,  
Drinkard Field, Lea County County.

The dates of this work were as follows: June 10-11, 1946

Notice of intention to do the work was ~~correct~~ submitted on Form C-102 on June 10 19 46  
and approval of the proposed plan was ~~correct~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On June 11, 1946, after fourteen hours had elapsed since running 7-5/8" OD 24# and 26.4# New Casing in subject well and cementing with 500 sacks cement, to be used as intermediate string, Pipe was tested with 1000# for one hour before drilling plug. Tested OK. Cement plug was then cored and specimens brought to surface indicated cement had set satisfactorily. After drilling out cement plug, pressure was built up to 1000# and held satisfactorily for one hour, indicating shut off. Drilling was resumed.

Witnessed by James E. Fox, Jr. Stanolind Oil & Gas Company Jr. Engr.  
Name Company Title

Subscribed and sworn before me this 12th

I hereby swear or affirm that the information given above is true and correct.

day of June, 19 46

Name Joseph L. Knudsen

Position Field Superintendent

Representing Stanolind Oil & Gas Company  
Company or Operator

My commission expires 2-23-50

Address Box "F", Hobbs, N. M.

Remarks:

APPROVED  
JUN 14 1946

Ray Yarbrough  
Name  
Oil & Gas Inspector  
Title