

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Perf Casing	xx

Hobbs, New Mexico October 14, 1943.

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corp - Gypsy Prod Div - J.F. Janda "E" State Well No. 1 in the

Company or Operator NE/4 of Sec. 21, T. 23S, R. 36E, N. M. P. M.,  
Lynn Field, Lea County.

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on 19

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

July 14, 1943 - Perforated casing by Lane-wells from 3500-36' incl., 10 holes w/4' spacing (No increase in gas)

August 31, 1943 perforated casing by Lane-Wells w/43 holes from 3564' to 3460'.

Sept 25, 1943 Acidized down casing thru perforations from 3567'-3460' w/1000 gallons 15% acid by Chemical Process Co.

2" Tubing set at 3702'3", 2" EUE x 5 1/2" OD Robinson Hook-Wall Packer at 3567'3", 136' of anchor below packer, Bryon by pass seating nipple at 3499'7", w/ 6 - 2" EUE Bryan Universal flow valves at 787'6", 1073'4", 1357'3", 1640'1", 1926'9", and 2210'6"

Production before - Well was dead - Prod After:- Flowed 30 brls oil and 1030 brls Water in  
Witnessed by 24 hours.

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

14th day of October, 1943

Name J. W. Anderson

Position District Supt.

Representing Gulf Oil Corp - Gypsy Prod Div.  
Company or Operator

My commission expires February 25, 1946.

Address Hobbs, New Mexico.

Remarks:

Roy. Garbrough  
Name  
Title