

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil & Gas Division  
1625 N. French Dr.  
Hobbs, NM 88240

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco Exploration & Production, Inc.

3. Address and Telephone No.

P. O. Box 3109, Midland, TX 79702 (915) 688-4438

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter O, 700' FSL, 2100' FEL  
Section 31, Township 22S, 38E

5. Lease Designation and Serial No.  
LC-032104 (R)

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. A.H. Blinberry  
FED NCT - 4 #3

9. API Well No.  
30-025-20211

10. Field and Pool, or Exploratory Area  
Brunson Drinkard

11. County or Parish, State  
Lea, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other \_\_\_\_\_  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- Set 2 7/8" CIBP @ 6050' (Tubb) Fill 2 7/8" csg w/120 sx cmt 6050' - 1500', covers (Queen, Yates & B-Salt)
- Cut 2 7/8" csg @ 1500', L/D csg. Spot 100 sx cmt plug 1500' - 1200' (T-Salt - 8 5/8 shoe) WOC Tag
- Displace hole w/salt gel mud, 9.5# brine w/25# gel P/BBL
- Spot 10 sx plug 10' - surf, install dry hole marker

14. I hereby certify that the foregoing is true and correct

Signed

Title

Date

(This space for Federal or State office use)

Approved by

(ORIG. SGD.)

GARY GOURLEY

Title

REGIONAL ENGINEER

Date

AUG 21 2000