		.*		
 			RES	

NEW MEXICO OIL OPNSERVATION COMMISSION

Santa Hr. New Mexico

[WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

LOCATE WEL	L CORRECTLY						State	
Marath	non Oil company				_Stat	e McDona	ld/A/C l-B	,
	(company or operate					(
Well No. 33	in SW	14 of <u>NE</u>		c 25	, Т	22 - S	, r	, NMPM.
Sout	th Eunice		Poo	l,		Lea		County
	feet from							
of Section 25	J	te Land the Oil	and Gas L	ease No. is	A 2614			
Drilling Commenced	11/4/63		, 19	. Drilling wa	Completed.	11/1	4/63	19
Name of Drilling Co	Iowe D	rilling Co	ompany	****		******	******	*****
Address	Box 83	2 - Midla	nd, Texa	19				
Elevation above sea le	evel at Top of Tubing	Head	3442 •		The inf	ormation give	n is to be kept c	onfidential unti
******		., 19						
		·	OIL SAND	s or zone	15			
No. 1, from) i	37761		. No. 4, fro	m	•	to	
No. 2, from	to			No. 5, fro	m		to	• • • • • • • • • • • • • • • • • • •
No. 3, from	to			. No. 6, fro	m	*****	to	,

IMPORTANT WATER SANDS

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
	26	New	1402	Guide			Surface
1-1/2	9.5		3792	11	· .	· · · · · · · · · · · · · · · · · · ·	Prod

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CABING	WHERE SET	NO. SACES OF CEMENT	METROD USED	MUD Gravity	AMOUNT OF MUD USED
11"	7-5/8	415	300	l plug		
6-3/4"	4-1/2	3801	975	11		
• <u> </u>						
						•

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treated thru perfs from 3766 - 69' w/500 gal mud acid & w/15,000 gal oil & 24,000 # sand w/1/20# Adomite per gal, in two stages.

Result of Production Stimulation....

Depth Cleaned Out.....

•	•	SOURD	OF DELLOTE	A AND SPACIAL I	b	
1	f drill-stem or other	special tests or dev	riation surveys were	made, submit report on	sepa	rate sheet and attach hereto
			TOOLS	USED		•
Rotary tools w	vere used from	0feet	<u>3802</u>	feet, and from		feet tofeet.
						feet tofeet.
			PRODU	OTION		
Put to Produc	ing 11/28/6	3	, 19			
OIL WELL:	The production du	16 ring the first XX ho	urs was 46	barrels	of lie	guid of which 100 % was
GAS WELL:	Gravity	0 @ 60 ⁰ Fo ring the first 24 ho h. Shut in Pressurc.	urs wasibs.			% was sediment. A.P.I.
	ne Shut in					
	So	utheastern New I		ORMANCE WITH GE	EOGI	RAPHICAL SECTION OF STATE): Northwestern New Mexico
T. Anhy	1380 (207	<u>2)</u> т.	Devonian	·····	Т.	Ojo Alamo
T. Salt		<u>с)</u> т.				Kirtland-Fruitland
B. Salt						Farmington
T. Yates T. 7 Rivers	3629 (- 17	5) 7) т.				Pictured Cliffs
	2/02 / 22	0 \				Menefee
T. Queen		т.лТ.	Ellenburger		Т.	Point Lookout

FORMATION RECORD

T. Ellenburger.....

Granite.....

•••••••

Gr. Wash.....

.....

.....

.....

Т.

Т.

Т.

Т.

Т.

Т.

Т.

T.

Т.

Т.

Т.

Т.

Т.

Т.

Т.

Т.

Т.

Point Lookout.....

Mancos.....

Dakota.....

Morrison.....

Penn

.....

From	То	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
0 290 1380 2811 3045 3146 3291 3695 3745 3796	290 1380 2811 3045 3146 3291 3695 3745 3796 3802	1090 1431	Sand, Gravel Redbed, Anhy Anhy, Salt Anhy Anhy, Gyp Anhy, Lime Lime Anhy, Dolo, Sand Anhy, Dolo, Sand Lime		ELEC	TRIC L	OG TOPS ABOVE
	,		•				- `````-

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

allet mechlor, J- 12/10/63 Address Box 220 - Hobbs, New Mexico

Company or Operator Marathon 011 Company

Name.....

Т.

Т.

T.

T.

Т.

T.

Т.

Т.

Т.

Grayburg.....

San Andres.....

Glorieta

Abo.....

Penn.....

Drinkard.....

Tubbs.....

Miss

Title Asst. Supt. Poni