

COUNTY	LEA	FIELD	Blinebry	STATE	N.M.
OPR	PHILLIPS PETROLEUM COMPANY				MAP
1 New Mexico "D"					
Sec. 36, T-22-S, R-37-E				CO-ORD	
1930' fr N Line & 660' fr E Line of Sec.					
Spud 5-30-64		CLASS		EL 33178	
Comp 7-30-64		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING	LOG	Anhy 1148			
		Yates 2530			
9 5/8" 1250' 480		SA 3892			
7" 7050' 1805 (Part-ed)		Glor 5072			
		Bli 5462			
4 1/2" 6895' 275		Tubb 5960			
LOGS EL GR RA IND HC A		Drkd 6140			
TD 7867', PBD 6893'					

IP Blinebry Perfs 5579-5670' Flwd 366 BOPD. Pot. Based on 24 hr test thru 24/64" chk., TP 1000#, CP 1400#, gravity 40.3, GOR 6200.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Lowe Drlg. Co. PROP DEPTH 7900' TYPE
DATE

F.R. 6-4-64
PD 7900' - Ellenburger
Contractor - Lowe Drlg. Co.
6-2-64 TD 1250', running 9 5/8" casing.
6-8-64 Drlg. 3795'.
6-15-64 Drlg. 5552'.
6-22-64 Drlg. 6734'.
6-29-64 Drlg. 7653'.
7-6-64 TD 7857', on DST.
Ran Logs.
7-13-64 TD 7867', prep to perf.
DST (Simpson) 7515-7857', open 1 hr,
Rec 20' DM,
30 min ISIP 380#, FP 30-30#,
1 hr FSIP 137#.
(No Ellenburger present in well)
7-20-64 TD 7867', fshg.
7" casing parted @ 4987'.

7-27-64 TD 7867', PBD 6893', tstg.
Perf 7" casing 6935-40' W/4 SPF
Ran 4½" casing.
Squeezed perfs 6935-40' W/450 sx.
Perf (Blinebry) 5579-82', 5604-07',
5644-50' & 5658-70' W/2 SPF
Ac. 1500 gals.
Flwd 3 BO/30 mins, TP 80#.

8-3-64 TD 7867', PBD 6893', COMPLETED.
Swbd 12 BAW + 11 BO in 11 hrs.
Frac 20,000 gals oil + 20,000# sd. 5579-5670'
Completed as a single producer in the Blinebry
Pool.
(Holding for tops)

8-10-64 TD 7867', PBD 6893', Completion Reported.
LOG TOPS: /Simpson 7345', Granite Wash
7577'. /Abc 6510',