

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP DATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

LC-032104

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NONE

7. UNIT AGREEMENT NAME

NONE

8. FARM OR LEASE NAME

A. H. Blinebry NCT-1

9. WELL NO.

20

10. FIELD AND POOL, OR WILDCAT

Blinebry - Tubb - Drinkard

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Sec. 20, T-22-S, R-38-E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. NAME OF OPERATOR TEXACO Inc.	
3. ADDRESS OF OPERATOR P. O. Box 728 - Hobbs, New Mexico	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Well located 1980' from the North Line, and 660' from the West Line of Section 20, T-22-S, R-38-E, Lea County, New Mexico.	
14. PERMIT NO. Regular	15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3398' (D. F.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth - 7200'

9 5/8" O. D. Casing Cemented at 1336'

Blinebry Zone: Ran 7188' of 2 7/8" O. D. Casing, 6.50 LB, New J-55, and cemented at 7198', RA collar with 2' sub at 5534', Plug at 7168'.

Tubb Zone: : Ran 7187' of 2 7/8" O. D. Casing, 6.50 LB, NEW J-55, and cemented at 7198', RA collar with 2' sub at 6096', Plug at 7167'.

Drinkard Zone: Ran 7187' of 2 7/8" O. D. Casing, 6.50 LB, NEW, J-55 and cemented at 7198', RA collar with 6' sub at 6880', Plug at 7167'.

Cemented after spot of 500 gals acetic acid with 400 Sx. Class "C" 8% gel with FRA, and 400 Sx. Class "C" 4% gel, 500 gals acetic acid behind each plug. Tested above strings of 2 7/8" O. D. Casing for 30 minutes with 2000 P. S. I. Tested O. K. Job complete 1:00 P. M. December 18, 1964.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. D. Raymond

TITLE

Assistant District Superintendent

DATE

December 22, 1964.

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

DEC 22 1964

*See Instructions on Reverse Side

L. GORDON
ACTING DISTRICT ENGINEER