

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPL
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC-032104

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NONE

7. UNIT AGREEMENT NAME

NONE

8. FARM OR LEASE NAME

A. H. Blinebry NCT-1

9. WELL NO.

21

10. FIELD AND POOL, OR WILDCAT

Blinebry & Drinkard

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20, T-22-S, R-38-E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
TEXACO Inc.

3. ADDRESS OF OPERATOR
P. O. Box 728 - Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
Well located 1980' from the West Line, and 660' from the
South Line of Section 20, T-22-S, R-38-E, Lea County, N. M.

14. PERMIT NO.
Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3400' (D. F.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Total Depth - 7100'
7 5/8" O. D. Casing cemented at 1336'

BLINEBRY ZONE: Ran 7077' of 2 7/8" O. D. Casing, 6.50 LB, NEW, J-55, and cemented
at 7089', RA collar on 8' sub at 5276', Plug at 7056'.

DRINKARD ZONE: Ran 7088' of 2 7/8" O. D. Casing, 6.50 LB, NEW, J-55, and cemented
at 7100', Plug at 7092'.

Cemented above strings of 2 7/8" O. D. Casing with 250 Sx. Class "C" 8% gel, plus
350 Sx. Class "C" 4% gel. Pump plugs down with 500 gals acetic acid. Tested 2 7/8"
O. D. Casing for 30 minutes from 3:30 P. M. to 4:00 P. M. January 21, 1965 with
2000 P. S. I. Tested O. K. Job complete 4:00 P. M. January 21, 1965.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. Raymond

TITLE Assistant District
Superintendent

DATE January 22, 1965.

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER