

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons.
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 100M-0115
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco E&P Inc.

3. Address and Telephone No.

P.O. Box 3109 Midland, Texas 79702 (915) 688-4492

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980 FSL 1980 FWL Sec 20 T22S R38E Unit Letter K

5. Lease Designation and Serial No.

41655

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

A.H. Blinbry Fed NCT-1#2

9. API Well No.

30-025-21050

10. Field and Pool, or Exploratory Area

Brunson Drinkard

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Notify BLM of intent to plug
2. MIRU on X string NU BOP
3. Set 2 7/8" CIBP @ 6950 w/20' cement
4. RIH circulate hole w/9.8# mud
5. 10 sx cement 6100-6000
6. 10 sx cement 5600-5500
7. 10 sx cement 5200-5100
8. POH NU on Y string
9. Set 2 7/8" CIBP @ 5550' w/ 20' cement
10. 10 sx cement 5200-5100
11. Cut and pull 2 7/8" casing(X&Y) 3000'±
12. 30 sx cement 3000-2900 WOC/tag
13. 30 sx cement 2600-2500 WOC/tag (Yates)
14. 40 sx cement 1430-1330 WOC/tag (salt/shoe)
15. 30 sx cement 1260-1160
16. 10 sx cement 30' to surface
17. RDMO, cut off well head, install dry hole marker, clean location.

Y-Blinebry
X-Drinkard

RECEIVED
1998 MAY -4 P 2:47
BUREAU OF LAND MGMT.
HOBBS, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed David W. Keap

Title Reservoir Engineer

Date 4/28/98

(This space for Federal or State office use)

Approved by ORIG SCD GARY GOURLEY

Title PETROLEUM ENGINEER

Date MAY 14 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.