

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for opening or plugging back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

|  |  |   |
|--|--|---|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/>  |  | 5. LEASE DESIGNATION AND SERIAL NO.<br>LC-032104                            |
| 2. NAME OF OPERATOR<br>TEXACO Inc.   |  | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME<br>NONE                                |
| 3. ADDRESS OF OPERATOR<br>P. O. Box 728 - Hobbs, New Mexico  |  | 7. UNIT AGREEMENT NAME<br>NONE  |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*<br>See also space 17 below.)<br>At surface<br>Well located 1980' from the West Line, and 1980' from the South Line of Section 20, T-22-S, R-38-E, Lea County, N. M. |  | 8. FARM OR LEASE NAME<br>A. H. Blinebry NCT-1                               |
| 14. PERMIT NO.<br>Regular  |  | 9. WELL NO.<br>22   |
| 15. ELEVATIONS (Show whether DF, RT, OR, etc.)<br>3400' (D. F.)  |  | 10. FIELD AND POOL, OR WILDCAT<br>Blinebry                                  |
|  |  | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA<br>Sec. 20, T-22-S, R-38-E |
|  |  | 12. COUNTY OR PARISH<br>Lea   |
|  |  | 13. STATE<br>N. M.  |

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Total Depth - 7150'  
8 5/8" O. D. Casing Cemented at 1375'

Blinebry Zone: Ran 7134' of 2 7/8" O. D. Casing, 6.50 LB, J-55, New, and cemented at 7148', 8' sub at 6790', Plug at 7138'.

Drinkard Zone: Ran 7133' of 2 7/8" O. D. Casing, 6.50 LB, J-55, NEW, and cemented at 7147', 6' sub at 5500', Plug at 7116'.

Cemented above strings of 2 7/8" O. D. Casing with 400 Sx. Class "C" 8% gel with FRA, plus 400 Sx. 4% gel. Pump plugs down with 500 gals acetic acid. Tested for 30 minutes with 2000 P. S. I. from 4:30 P. M. to 5:00 P. M. February 13, 1965. Tested O. K. Job complete 5:00 P. M. February 13, 1965.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. D. Raymond

TITLE

Assistant District  
Superintendent

DATE February 15, 1965.

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

FEB 16 1965

\*See Instructions on Reverse Side  
S. L. GORDON  
ACTING DISTRICT ENGINEER