

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instructions
verse side)

TE-
re

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. LC-032104
2. NAME OF OPERATOR TEXACO Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME NONE
3. ADDRESS OF OPERATOR P. O. Box 728 - Hobbs, New Mexico		7. UNIT AGREEMENT NAME NONE
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Well located 1980' from the West Line, and 1980' from the South Line of Section 20, T-22-S, R-38-E, Lea County, N.M.		8. FARM OR LEASE NAME A. H. Blinebry NCT-1
14. PERMIT NO. Regular		9. WELL NO. 22
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3381' (GR)		10. FIELD AND POOL, OR WILDCAT Blinebry
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20, T-22-S, R-38-E
		12. COUNTY OR PARISH Lea
		13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth - 1375'
Spudded 11" Hole at 6:00 A. M. January 22, 1965

Ran 1361' of 8 5/8" O. D. Casing, 17.28 LB, Spiral Weld, NEW, and cemented at 1375' with 400 Sx. Class "C" 4% gel, plus 200 Sx. Class "C" neat with 2% CACL. Plug at 1345'. Cement Circulated. Job complete 1:30 P. M. January 24, 1965.

Tested 8 5/8" O. D. Casing for 30 minutes with 600 P. S. I. from 10:30 P. M. to 11:00 P. M. January 24, 1965. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 1:45 A. M. to 2:15 A. M. January 25, 1965. Tested O. K. Job complete 2:15 A. M. January 25, 1965.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. D. Raymond
H. D. Raymond

TITLE

Assistant District
Superintendent

DATE January 25, 1965.

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JAN 26 1965

*See Instructions on Reverse Side J. L. GORDON
ACTING DISTRICT ENGINEER