

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions
reverse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032100

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NONE

7. UNIT AGREEMENT NAME

NONE

8. FARM OR LEASE NAME

C.H. Lockhart Federal NCT-1

9. WELL NO.

10

10. FIELD AND POOL, OR WILDCAT

Drinkard

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 18, T-22-S, R-38-E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. NAME OF OPERATOR TEXACO Inc.	3. ADDRESS OF OPERATOR P. O. Box 728 - Hobbs, New Mexico	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface well located 660' from the East Line, and 1980' from the North Line of Section 18, T-22-S, R-38-E, Lea County, N. M.
14. PERMIT NO. Regular	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3376' (D. F.)	12. COUNTY OR PARISH Lea	13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☒MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth - 1350'
Spudded 11" Hole at 6:00 A. M. August 7, 1964

Ran 1338' of 7 5/8" O. D. Casing, 24.00 LB, H-40, NEW, and cemented at 1350' with 500 Sx. Class "C" 4% gel, plus 100 Sx. Class "C" neat with 2% CACL. Plug at 1318'. Cement Circulated. Job complete 4:15 A. M. August 9, 1964.

Tested 7 5/8" O. D. Casing for 30 minutes with 800 P. S. I. from 3:30 P. M. to 4:00 P. M. August 10, 1964. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 800 P. S. I. 5:00 P. M. to 5:30 P. M. August 10, 1964. Tested O. K. Job complete 5:30 P. M. August 10, 1964.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. D. Raymond

TITLE

Assistant District Supt.

DATE

September 3, 1964

(This space for Federal or State office use)

APPROVED BY

TITLE

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

SEP 4 1964

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER