

COUNTY	LEA	FIELD	Langlie-Mattix	STATE	NM
OPR	HUMBLE OIL & REFG. CO.				MAP
WS-2 New Mexico State "M"					
Sec. 29, T-22-S, R-37-E				CO-ORD	
660' FNL & 200' FWL of Sec.					
Spd 5-9-65		CLASS		EL	
Cmp 11-12-65		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING					
9 5/8"	295'	250			
7"	5006'	600			
LOGS EL GR RA IND HC A					
		TD 5006', PBD 4999'			

WATER SUPPLY WELL

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 4500'	TYPE
DATE		

F.R. 4-29-65; Water Supply Well
PD 4500' - SA
5-10-65 TD 295', WOC.
5-17-65 Drlg. 3872'.
5-24-65 TD 5006', PBD 4999', WOC.
6-1-65 TD 5006', PBD 4999', SI for Pressure Buildup.
Perf @ 4902', 4904', 4930', 4934', 4936',
4945', 4948', 4950', 4954', 4956', 4959',
4960', 4970', 4972', 4975', 4977', 4979',
4981', 4983', 4985' W/1 SPI
Ac. 5000 gals.
Perf 4697-4727', 4737-52', 4778-93',
4838-40', 4844-54', 4859-63', 4871-83'
W/1 shot per two feet
Set SP @ 4890'
Ac. 10,000 gals.

5-7-65 TD 5006', PED 4999', swbg.
Pulled BP @ 4890'
Perf @ 4456', 4458', 4460', 4462', 4464',
4466', 4468', 4470', 4472', 4482', 4484',
4486', 4488', 4490', 4492', 4603', 4605',
4607', 4609', 4611', 4613', 4615', 4617',
4619', 4629', 4633', 4635', 4637', 4638',
W/1 SPI
Perf 4442-54', 4660-76' W/1 SPI
Set BP @ 4587'
Ac. 10,000 gals. (4442-4676')
Perf 4425-92' W/35 shots
Re-Set BP @ 4500'
Ac. 10,000 gals. (4425-92')

6-14-65 TD 5006', PED 4999', RJ Pump.
Pulled BP @ 4500'
6-21-65 TD 5006', PED 4999', RJ Pump.
6-28-65 TD 5006', PED 4999', RJ Pump.
7-6-65 TD 5006', PED 4999', RJ Pump.
7-12-65 TD 5006', PED 4999', RJ Pump.
7-19-65 TD 5006', PED 4999', RJ Pump.
7-26-65 TD 5006', PED 4999', RJ Pump.
(Pinal posting until status changes)
11-22-65 TD 5006', PED 4999', COMPLETED.
Completed as Water Supply Well with
perfs 4425-4985'