

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instruction
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. LC-032104
2. NAME OF OPERATOR TEXACO Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME NONE
3. ADDRESS OF OPERATOR P. O. Box 728 - Hobbs, New Mexico		7. UNIT AGREEMENT NAME NONE
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Well located 1980' from the East Line, and 660' from the North Line, of Section 29, T-22-S, R-38-E, Lea County, N. M.		8. FARM OR LEASE NAME A. H. Blinebry NCT-1
14. PERMIT NO. Regular		9. WELL NO. 26
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3377' (GR)		10. FIELD AND POOL, OR WILDCAT *See below
		11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec. 29, T-22-S, R-38-E
		12. COUNTY OR PARISH Lea
		13. STATE N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *Paddock, Blinebry, Drinkard

Total Depth - 1394'
Spudded 12 1/4" Hole at 9:30 A. M. June 10, 1965

Ran 1381' of 9 5/8" O. D. Casing, 25.45 LB, Spiral Weld, New, and cemented at 1394' with 260 Sx. Class "C" cement with 2.3 Lb. salt per sx & 2% CACL., plus 210 Sx. Trinity Lite Wate, and 200 Sx. Class "C" cement with 1% CACL. Plug at 1364'. Cement Circulated. Job complete 8:00 A. M. June 12, 1965.

Temperature of mixing slurry - 72 degrees, 12 Hour Strength 1000 P. S. I.
Bottom Hole Temperature - 76 degrees - Water Temperature - 72 degrees.

Tested 9 5/8" O. D. Casing for 30 minutes with 600 P. S. I. from 9:00 P. M. to 9:30 P. M. June 12, 1965. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 10:00 P. M. to 10:30 P. M. June 12, 1965. Tested O. K. Job complete 10:30 P. M. June 12, 1965.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. D. Raymond

TITLE

Assistant District
Superintendent

DATE

June 15, 1965

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

JUN 16 1965

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER