

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

AUG 31 2 53 PM '65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.
Fee

7. Unit Agreement Name
NONE

8. Farm or Lease Name
W. L. Nix

9. Well No.
5

10. Field and Pool, or Wildcat
Drinkard

12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)
Not Available

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
--

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.
--

SIGNED <u>J. E. Jordan</u>	TITLE <u>Field Foreman</u>	DATE <u>August 31, 1965</u>
----------------------------	----------------------------	-----------------------------

APPROVED BY _____	TITLE _____	DATE _____
-------------------	-------------	------------

CONDITIONS OF APPROVAL, IF ANY:
---------------------------------

Total Depth - 1413'  
Spudded 11" Hole at 4:15 P. M. August 26, 1965

Ran 1401' of 8 5/8" O. D. Casing, 20.00 LB, Spiral Weld, NEW, and cemented at 1413' with 430 Sx. Trinity Lite Wate, plus 100 Sx. Class "C" neat with 1% CC. Plug at 1385'. Cement Circulated.

Temperature of mixing slurry - 90°, Strength 12 Hours 1000 P. S. I.  
Bottom Hole Temperature - 78°, Job complete 4:30 A. M. August 28, 1965.

Tested 8 5/8" O. D. Casing for 30 minutes with 600 P. S. I. from 4:00 P. M. to 4:30 P. M. August 28, 1965. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 5:00 P. M. to 5:30 P. M. August 28, 1965. Tested O. K. Job complete 5:30 P. M. August 28, 1965.