

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on plugging and abandoning well.	X

April 25, 1949  
DateHobbs, New Mexico  
Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Gulf Oil Corporation J. F. Janda "E" Well No. 2 in the \_\_\_\_\_  
 Company or Operator Lease  
NE/4 of Sec. 21, T. 23S, R. 36E, N. M. P. M.,  
Lynn Field, \_\_\_\_\_ Lea \_\_\_\_\_ County.

The dates of this work were as follows: Started April 16, 1949. Completed April 23, 1949.  
 Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on January 27, 1949  
 and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran tubing to 3415' and mudded hole to surface. Spotted 5 sacks of cement @ 2800' and pulled tubing. Shot 5½" casing off @ 2100', and recovered 2086' (87 jts.). Ran tubing to 2075', mudded hole to surface, and spotted ten sacks of cement @ 2075'. Shot 7-5/8" @ 1950', 1850', 1750', 1530', 1450', 1350', 1250', 1150', 1050', 900', 800', 700', 600', 550', and 470'. Recovered 470' (21 jts.) of 7-5/8" casing. Ran tubing to 470', mudded hole to surface, spotted 6 sacks of cement in top of 10-3/4" casing, pulled tubing, and set regulation marker on surface.

Witnessed by C. C. Brown Gulf Oil Corporation Production Foreman  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_  
25th day of April 1949

I hereby swear or affirm that the information given above is true and correct.

Name J. F. Janda  
 Position District Sup't.

Representing Gulf Oil Corporation  
 Company or Operator

My commission expires 10-24-49Address Box 1667, Hobbs, New Mexico

Remarks:

APPROVED  
 APR 28 1949  
 Let's

W. D. Gallagher  
 Name