6 <u>Nar</u> , W. 1. <u>Sec. 19</u> , <u>M.22</u> -5, <u>R-38</u>	}∞E	CO-ORD MATERIA CLASS EL		
1980' FST, 1650' FWL Spd 5-36-66	91 360.			L
0mp 6-16-16	FORMATION	DATUM	FORMATION	DATUN
CSG & SX - TUBING				
7 5/8" 1+00' 600				
2 7/8" 300' 800				
LOGS EL GR RA IND HC A				
TP Frinkarc Perfs 7056-7	TD 7308',	<u>PED 7292'</u>		

Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.						
CONT. R.CHRIS Drlg. Co.	<u>ргор дертн 730</u>	0 TYPE				

5~31~65	F.R. 5-26-66 PB 7300' - Drinkard Contractor - Rod Ric TD 1400', prep to run casing.	
6-6-66	Drlg. 4196'.	1
6-13-66	Dr1g. 6037'.	i
6-20-66	The 7300', fishing drill pipe.	1
6-27-66	TD 7300', PBD 7292', COMPLETE.	1
	Part @ 7056', 7065', 7071', $7073'$ , $9098'$	
	二 661、 71861、 72051、 72121、 72161、 72311、	
	7235', 7250', 7260', 7267', 7273', 7483',	
	70881, 72901, 72931 W/2 SPI	
	ac (7056-7293') 15,000 gals 15%; 1R /. T EFF.	
	TOG TOPS: Yates 2778', San Andres 4240',	
	Blinebry 5842', Tubb 6408', Abc 6925'.	

## OIL CONSERVATION COMMISSION P. O. BOX 871 SANTA FED NEW MEXICO

JUL 11 8 09 M '66

July 7, 1966

Texaco Inc. Drawer 728 Hobbs, New Mexico 88240

Attention: Mr. Dan Gillett

Gentlemen:

Reference is made to your letter dated June 24, 1966, wherein you request authority to complete your W. L. Nix Well No. 6 located 1980 feet from the South line and 1650 feet from the West line of Section 17, Township 22 South, Range 38 East, Lea County, New Mexico, as a tubingless completion in the Drinkard Pool.

It is our understanding that 2 7/8-inch casing will be set at approximately 7300 feet and perforated from approximately 7056 feet to 7290 feet in the Drinkard formation. Sufficient cement will be used to come back to the base of the salt expected at 2600 feet.

Texaco Inc. is hereby authorized to complete the subject well in the aforesaid manner.

Very truly yours,

A. L. PORTER, Jr. Secretary-Director

ALP:DSN:sg cc: Oil Conservation Commission - Hobbs Oil & Gas Engineering Committee - Hobbs Well File



. . . . . Jul 11 6 69 63 36

June 24, 1966

New Mexico Oil Conservation Commission P.O. Box 2088 Santa Fe, New Mexico

> Re: Application for Single Tubingless Completion, TEXACO Inc. W. L. Nix Well No. 6, Drinkard Pool, Lea County, New Mexico.

Attention: Mr. A. L. Porter, Jr.

Gentlemen:

TEXACO Inc. respectfully requests administrative approval of an exception to Statewide Rule 107(e) to authorize the tubingless completion of W.L. Nix Well No. 6 in the Drinkard Pool. This well is located 1980 feet from the South line and 1650 feet from the West line of Section 17, Township 22 South, Range 38 East, Lea County, New Mexico.

Surface casing consists of 7-5/8 inch pipe set at 1400 feet and cemented to surface with 400 sacks of Trinity Lite Wate cement plus 200 sacks of Class 'C' cement. Production casing shall consist of 2-7/8 inch pipe to be set at total depth of approximately 7300 feet and is to be cemented with 400 sacks of Trinity Lite Wate cement plus 400 sacks Class 'C' with 4% gel. The calculated cement volume equals 140% of the calculated annular volume from total depth to the base of the salt at approximately 2600 feet.

No corrosion or paraffin problems have been encountered in wells previously completed in the Drinkard Pool. The New Mexico Oli Conservation Commission has previously authorized the tubingless completion of a well in the Drinkard Pool in TEXACO inc. W. L. Nix Well No. 5.

Yours very truly.

(and lett Dan Gillett

Assistant District Superintendent

LMF-bh

NMOCC-Hobbs Offset Operators Attachments