State of New Mexico Submit 3 Copies To Appropriate District Form C-103 Office Energy, Minerals and Natural Resources Revised March 25, 1999 District I WELL API NO. 1625 N. French Dr., Hobbs, NM 87240 District II 30-025-22159 OIL CONSERVATION DIVISION 811 South First, Artesia, NM 87210 5. Indicate Type of Lease 2040 South Pacheco District III 1000 Rio Brazos Rd., Aztec, NM 87410 STATE X FEE \square Santa Fe. NM 87505 District IV 6. State Oil & Gas Lease No. 2040 South Pacheco, Santa Fe, NM 87505 LC-058626-A SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name: (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) LANGLIE-MATTIX PENROSE SAND UNIT 1. Type of Well: TRACT 24 Oil Well Gas Well Other INJECTION 2. Name of Operator 8. Well No. Anadarko Petroleum Corp. 24-04 3. Address of Operator 9. Pool name or Wildcat P.O. Box 2497 Midland, TX 79702 LANGLIE-MATTIX SR QN GRBG 4. Well Location 1330 SOUTH 1330 **EAST** feet from the line and feet from the line Section 28 Township Range 37E **NMPM** County **LEA 22S** 10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3346' GL 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK **ALTERING CASING** \square **TEMPORARILY ABANDON CHANGE PLANS** X COMMENCE DRILLING OPNS. **PLUG AND ABANDONMENT CASING TEST AND PULL OR ALTER CASING** MULTIPLE COMPLETION **CEMENT JOB** OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation. DECISION HAS BEEN MADE TO PLUG ABANDON WELL IN LIEU OF REPAIR. 1. MIRU. TIH W/TBG. CIRC W/MUD. SPOT 25 SX CMT ON RBP @ 3431'. 2. PERF @ 2540'. SOZ 25 SX FROM 2540 - 2440'. 3. PERF @ 1280'. SQZ 25 SX FROM 1280 - 1180'. 4. PERF @ 367'. SQZ 35 SX FROM 367 - 267'. 5. PERF @ 60'. CIRC 20 SX TO SURF. CUT OFF WELLHEAD & INSTALL MARKER. **CONDITIONS OF APPROVAL** All pits must be lined with plastic All shoe plugs, stub plugs & cement plugs above perforations must All cement plugs pumped minimum 25 sxs & be minimum 100 feet a nereon certify that the jangimation above is true any complete to the loest of my knowledge and belief. TITLE SR STAFF PRODUCTION ENGINEER DATE. SIGNATURE. Type or print name R.N. MUELLER Telephone No. 915/683-0555 ORIGINAL STOMED BY (This space for State use) GARY VI TITLE OC FIELD REPRESENTATIVE ILISTAFF MANAGER EEB 1 9 2002 APPROVED BY_ Conditions of approval, if any: