

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Marathon Oil Company	8. Farm or Lease Name J. L. Muncy
3. Address of Operator P. O. Box 220, Hobbs, New Mexico	9. Well No. 4
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>24</u> TOWNSHIP <u>22S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) Not known at this time	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Cementing surface casing</u> <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 8-21-67. Drilled to 1400'. Ran 35 jts. of 9-5/8" casing, 1393.59' OA. Set from 13.00' below KD to 1399.00' Last setting depth includes Baker circ. flex flo collar and guide shoe 2.83'. Bottom 200' covered w/centr. Bottom 2 jts. Baker locked. Cemented by BJ Service w/190 sxs of Class C 1 - 1/3 Diemix & 4% Gel followed w/330 sxs of Class C, 2% Ca Cl₂. Pumping press. 500#. Circ. 45 sxs to pit. Cement dropped 30' after 30 min.. W.O.C. 24 hrs. Tested casing with 1200 lbs. for 30 min. Held O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. L. Helle TITLE Area Supt. DATE 8-31-67

APPROVED BY J. L. Muncy TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Dist.: LHS; BGH; CoPL; File