

WRS COMPLETION REPORT

COMPLETIONS SEC 19 TWP 22S RGE 38E
PI# 30-T-0023 08/22/88 30-025-22473-0001 PAGE 1

NMEX LEA * 640FSL 1650FWL SEC SE SW
STATE COUNTY FOOTAGE SPOT
HANSON CORP D X DO
OPERATOR WELL CLASS INIT FIN
5 GUTMAN MAX
WELL NO. LEASE NAME
3358KB BLINEBRY
OPER ELEV FIELD POOL AREA

API 30-025-22473-0001

LEASE TYPE NO. PERMIT OR WELL I.D. NO.
12/24/1987 12/25/1987 WO-UNIT OIL-WO
SPUD DATE COMP. DATE TYPE TOOL STATUS
5759 BLINEBRY NOT RPTD

PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 7447 PB 5759 OTD 7447 FM/TD GR WSH
DRILLERS I.D. LOG TO PLUG BACK TO OLD I.D. FORM I.D.

LOCATION DESCRIPTION

5 1/2 MI SE EUNICE, NM

TUBING DATA

TBG 2 3/8 AT 5759

INITIAL POTENTIAL

IPP 61BOPD 425 MCFD 39BW 24HRS
BLINEBRY PERF W/ 31/IT 5489- 5671 GROSS
PERF 5489- 5527 5574- 5671
ACID 5574- 5671 3000GALS
15% NEFE
ACID 5489- 5527 3000GALS
15% NEFE
SWFR 5574- 5671 50000GALS 90000LBS SAND

ADDTVGELA

20/40
SWFR 5489- 5527 50000GALS 95000LBS SAND

ADDTVGELA

20/40
GTY 37.0 GOR 6967

TYPE	FORMATION	LTH	TOP DEPTH/SUB	BSE DEPTH/SUB
LOG	SALT		1255 2103	2495 863
LOG	GLORIETA		5111 -1753	
LOG	PADDOCK		5138 -1780	
LOG	BLINEBRY		5480 -2122	

CONTINUED IC# 300257033288

COMPLETIONS SEC 19 TWP 22S RGE 38E
PI# 30-T-0023 08/22/88 30-025-22473-0001 PAGE 2

HANSON CORP D X DO
5 GUTMAN MAX

TYPE	FORMATION	LTH	TOP	DEPTH/SUB	BSE	DEPTH/SUB
LOG	TUBB		6062	-2704		
LOG	DRINKARD		6270	-2912		
LOG	ABO		6568	-3210		

SUBSEA MEASUREMENTS FROM KB

PRODUCTION TEST DATA

DRINKARD PERF				6392-	6963
GR WSH PERF				7356-	7391
PERF	6392-	6963	7356-	7391	
BRPG @ 5759			6392-	6963	7356- 7391

DRILLING PROGRESS DETAILS

HANSON CORP
BOX 1515
ROSWELL, NM 88202-1515
505-622-7330

OWWO: OLD INFO: FORMERLY HANSON ERNEST A #5
GUTMAN MAX. ELEV 3358 KB. SPUD 3/15/68. 8 5/8
@ 1180 W/450 SX, 5 1/2 @ 7447 W/425 SX. LOG
TOPS: GRAYBURG 3718, SAN ANDRES 3945, GRANITE
WASH 7352. OTD 7447. PB 7419. COMP 4/23/68.
IPF 260 BOPD. PROD ZONE: DRINKARD 6392-6963.
IPF 840 BOPD. PROD ZONE: GRANITE WASH 7356-7391.
DUAL PRODUCER.

08/16 LOC/1988/
08/16 7447 TD, PB 5759
COMP 12/25/87, IPP 61 BO, 425 MCFG, 39
BWPD, GOR 6967, GTY 37
PROD ZONE - BLINEBRY 5489-5671
FIRST REPORT & COMPLETION

COUNTY	LEA	FIELD Brunson, E. (Gr. Wash) / TE NM		
OPR	HANSON, ERNEST A.		/Drinkard	
	5	Gutman, Max	MAP	
	Sec. 19, T-22-S, R-38-E		CO-ORD	
	640' FSL, 1650' FWL of Sec.		30-025-22473	
	Spd 3-15-68; Cmp 4-23-68 (Drkd)		CLASS	EL [REDACTED]
	Cmp 4-20-68 (Gr. W)		FORMATION	DATUM
CSG & SX - TUBING			FORMATION	DATUM
8 5/8"	1180'	450		
5 1/2"	7447'	425		
LOGS EL GR RA IND HC A				
	TD 7447', PBD 7419'			

IP Drinkard Perfs 6392-6963' Flwd 260 BOPD. Pot. Based on 12 hr test of 130 BO thru 12/64" chk., TP 1000#, Gravity 39.
 IP Granite Wash Perfs 7356-91' Flwd 840 BOPD. Pot. Based on 8 hr test of 280 BO thru 1/2" chk., Gravity 39.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	Roy Smith	PROP DEPTH	7400'	TYPE	RT
DATE					

F.R. 3-21-68; Elev. 3358' KB
 PD 7400' - Drinkard/Gr. Wash
 Contr. - Roy Smith Drlg. Co.
 4-29-68 AMEND FIELD DESIGNATION: Formerly reported
 as Drinkard/Undesignated (Gr. Wash)
 3-25-68 Drlg. 4343'.
 Cored 2538-52', rec 6' being:
 2' grey sdy sh;
 4' dolo., w/NS.
 4-1-68 Drlg. 6275' lm & dolo.
 4-8-68 TD 7447', prep perf.
 DST 7341-7447', tool plugged
 rec 90' drlg mud.
 4-22-68 TD 7447', prep perf.

4-29-68 TD 7447', PED 7419', COMPLETE
Perf (Drinkard) @ 6392', 6398', 6411',
6421', 6433', 6441', 6451', 6460', 6468',
6505', 6511', 6523', 6528', 6535', 6543',
6549', 6558', 6671', 6688', 6697', 6715',
6728', 6741', 6750', 6765', 6781', 6796',
6855', 6862', 6875', 6885', 6891', 6903',
6917', 6928', 6945', 6953', 6963' W/l SPI
Acid (6392-6963') 10,000 gals.
Frac (6392-6963') 60,000 gals oil + 30,000#
sd.
Perf (Granite Wash) @ 7356', 7366', 7373',
7386', 7391' W/l SPI
Acid (7356-91') 6000 gals.
LOG: Anhy 1158', Yates 2540', Queen 3365',
Grayburg 3718', SA 3945', Granite Wash 7352'.