

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

JUL 22 3 10 PM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- Disposal Well		7. Unit Agreement Name
2. Name of Operator Warren Petroleum Corporation		8. Farm or Lease Name Bunice Plant No. 161
3. Address of Operator Box 1197, Bunice, New Mexico		9. Well No. SWD #1
4. Location of Well UNIT LETTER H 2255 FEET FROM THE North LINE AND 908 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 22-S RANGE 37-E N.M.P.M.		10. Field and Pool, or Wildcat San Andres
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cactus Drilling Company spudded 12 1/4" surface hole at 6:00 PM, July 19, 1968. Drilled to 1202'. Ran 38 joints, 1185' of 9-5/8" 36# J-55 ST&C casing. Set and cemented at 1198' with 400 sacks of Class C cement with 4% gel and 2% Ca Cl2 and 150 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC & NU over 18 hours. Tested casing with 1225#, 30 minutes, OK.

Started drilling 8-3/4" hole at 1202' at 2:30 AM, July 22, 1968.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY SIGNED <u>C. D. BORLAND</u>	TITLE <u>Area Production Manager</u>	DATE <u>July 22, 1968</u>
Agent for Warren Petroleum Corporation		
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		