

COPIES RECEIVED		
DISTRIBUTION		
SATISFACTION		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No. B-934	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- WATER SOURCE WELL		7. Unit Agreement Name
2. Name of Operator EXXON CORPORATION		8. Farm or Lease Name NEW MEXICO "S" STATE
3. Address of Operator P.O. Box 1600, MIDLAND, TEXAS 79701		9. Well No. WS-4 CP-427
4. Location of Well UNIT LETTER M , 650 FEET FROM THE WEST LINE AND 175 FEET FROM THE SOUTH LINE, SECTION 2 TOWNSHIP 22-S RANGE 37-E NMPM.		10. Field and Pool, or Wildcat EUNICE (SOUTH SAN ANTONIO)
15. Elevation (Show whether DF, RT, GR, etc.) DF 3383		12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-11-76, MIRU BABER, LAID DN 73 JTS 3 1/2" TBG, PICKED UP 2 3/8" TBG, UNABLE TO GET BELOW 2200'.

5-12-76, RAN 6 1/8" IMPRESSION BLK TO 2138', HAD PICTURE OF COLLAPSED CSG., RAN HALLIBURTON CMT RETAINER ON 2 3/8" TBG, SET @ 2100', PMPD INTO CSG @ 5 3/4 BPM, MP 1000#. UNABLE TO LOAD CSG ABOVE RETAINER W/135 BBLs WTR, PMPD 600 SX CL C WENT CMT BELOW RET, MP 500#, PLD OUT OF RET AND PLD 20 JTS TBG.

5-13-76, SPOT 50 SX CMT PLUG 1200-1100', WAIT 4 HRS, UNABLE TO TAG PLUG. SPOT 75 SX PLUG 1200-1100'.

5-14-76, TAGGED CMT PLUG @ 1100' FROM SURFACE. SPOT 24 SX CMT PLUG @ 1050' BACK TO 950'. 46 SX PLUG @ 350' BACK TO 750' AND 10' PLUG TO SURFACE. PMPD CMT PLUGS DOWN W/MLD LADEN BRINE, REMOVED WELLHEAD, INSTALLED DRY HOLE MARKER A.R.R. + F.R.W. 5-14-76.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *[Signature]* TITLE SECTION HEAD DATE 7-1-76

APPROVED BY *[Signature]* TITLE OIL & GAS INSPECTOR DATE 7-1-76

CONDITIONS OF APPROVAL, IF ANY: