

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instruction reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0450008

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Spear Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Drinkard Ext.

11. SEC., T., R., M., OR BLE, AND
SURVEY OR AREA

Sec. 21, T-22-S, R-38-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Lunar Oil & Gas

3. ADDRESS OF OPERATOR

Box 5596, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3367' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Plug and abandon

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed plugging procedure:

25 sx plug from 7100' to 7200'

25 sx plug from 6600' to 6700'

25 sx plug from 5500' to 5600'

25 sx plug in and out of stub. Shoot off 7" csg. at estimated 4000'

25 sx plug from 2800' to 2900'

25 sx plug from 1450' to 1550'

25 sx plug from 800' to 900'

10 sx plug @ surface. Set marker. Hole will be filled with
9.8# mud

18. I hereby certify that the foregoing is true and correct

SIGNED

M. J. Smith

TITLE

Production Clerk

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

OCT 7 1970

ARTHUR R. BROWN

DISTRICT ENGINEER

DATE 10-5-70

DATE

*See Instructions on Reverse Side

RECEIVED

SEP 18 1970

OIL CONSERVATION COM. 11.
U.S. DEPT. OF THE INTERIOR