

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER -		7. Unit Agreement Name
2. Name of Operator Gulf Oil Corporation		8. Field or Lease Name Drinkard (NCT-B)
3. Address of Operator Box 670, Hobbs, New Mexico 88240		9. Well No. 3
4. Location of Well UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 22-S RANGE 38-E N.M.P.M.		10. Field and Pool, or Wildcat Drinkard
15. Elevation (Show whether DF, RT, GR, etc.)		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moran Drilling Company spudded 12-1/4" surface hole at 6:00 PM, April 10, 1970. Drilled to 1267'. Ran 41 joints, 1253' of 8-5/8" OD 21# K-55 ST&C casing set and cemented at 1266' with 400 sacks of Class C with 4% gel and 2% Ca Cl2 and 225 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC and NU 18 hours. Tested casing with 1100#, 30 minutes, OK.

Started drilling 7-7/8" hole at 1267' at 4:30 AM, April 13, 1970.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY

C. D. BORLAND

SIGNED _____

TITLE **Area Production Manager**

DATE **April 13, 1970**

APPROVED BY _____

TITLE **SUPERVISOR DISTRICT**

DATE _____

CONDITIONS OF APPROVAL, IF ANY: