

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Stelts, Wagner & Brown 3. Address of Operator c/o Oil Reports & Gas Services, Inc. - Box 763 - Hobbs, New Mexico 4. Location of Well UNIT LETTER A , 330 FEET FROM THE North LINE AND 879 FEET FROM THE East LINE, SECTION 21 TOWNSHIP 22 S RANGE 37 E NMPM.	7. Unit Agreement Name 8. Farm or Lease Name Walden 9. Well No. 1 10. Field and Pool, or Wildcat Undes. So. McCormack 15. Elevation (Show whether DF, RT, GR, etc.) 3376 GR 12. County Lea
--	---

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 7:00 P.M. 9/11/70. Cemented 8 5/8" 24# H-40 casing at 1160 with 325 sacks Malliburton lite cement 3% Calcium Chloride with 1/4# flo-seal per sack and 300 sacks Class "C" cement 3% Calcium Chloride with 1/4# flo-seal per sack. Circulated out approximately 150 sacks. Plug down 1:00 P.M. 9/14/70. WOC 18 hours and pressure tested casing with 800# for 30 minutes, test OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>H. L. Smith</i></u>	TITLE <u>Agent</u>	DATE <u>9/22/70</u>
APPROVED BY <u><i>[Signature]</i></u>	TITLE <u>REGISTRAR DISTRICT</u>	DATE <u>10/1/70</u>
CONDITIONS OF APPROVAL, IF ANY:		