

COUNTY IFA FIELD Eunice, S. STATE NM 30-025-23606
 OPR ANADARKO PROD. CO. MAP
 S Wortham, Lou
 Sec 11, T-22-S, R-37-E CO-ORD
 990' TVL, 1650' FWL of Sec
 Spd 10-21-70
 Temp 12-20-70 CLASS EL 3370E
 LOG & SX - TUBING
 9 5/8" at 366' w/200 SX
 7" at 4750' w/450 SX
 LOGS EL GR RA IND MC A
 TD 4750'; PBD 4715'
 (San Andres) Perfs 4116-4250' P 183 EOED + 297 SW. Pot based
 on 24 hr test. COR 1820; Crav 34.3.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Logging Service, Inc.

CONT WEL PROP DEPTH 4800' TYPE RT
 DATE

W.R. 10-20-70; Opr's Elev. 3366' GL, 3375' KE
 WD 4800' RT (San Andres)
 Contractor - WELK
 10-27-70 WD 2460'; SD Repairs
 (Notes) blew out @ 2460' & rig caught fire
 11-10-70 TD 2460'; SD Repairs
 11-16-70 TD 2460'; SD Repairs
 11-23-70 Trlg. 3643' w/ky & lm
 11-30-70 W 4750'; Prep log
 at Cores or DST's
 12-1-70 TD 4750'; PBD 4715'; WCO
 12-16-70 TD 4750'; PBD 4715'; SWt
 Perf 4116-23', 4150-54', 4244-50' w/i SPF
 Acid (4116-4250') 9500 gals (28%)

LEA Eunice, S. NM Sec 11, T22S, R37E
ANADARKO PROD. CO. S. Wortham, Lou Page #2

12-21-70 TD 4750'; PSD 4715'; TO Pmp
12-28-70 TD 4750'; PSD 4715'; COMPLETE
LOG TOPS: Anhydrite 1080', Yates 2450',
Seven Rivers 2578', Queen 3400', Crayburg
3658', San Andres 3800'
12-31-70 COMPLETION REPORT