

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Danglade
9. Well No. 2
10. Field and Pool, or Wildcat Drinkard
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator John H. Hendrix
3. Address of Operator 316 Central Bldg., Midland, Texas 79701
4. Location of Well UNIT LETTER <u>A</u> . <u>330</u> FEET FROM THE <u>North</u> LINE AND <u>200</u> FEET FROM THE <u>East</u> LINE, SECTION <u>24</u> TOWNSHIP <u>22S</u> RANGE <u>27</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded @ 3:15 P.M. on November 7, 1970.
- Drilled 12½" hole to 1247' KB.
- Run Texas Pattern Shoe, 310' (7jts) of new 24# 5-95 STSC and 924' (27 jts) of new 20# L-46 set @ 1247'.
- Cemented w/10 sax Class C 50:50 Pozmix w/4% gel and 200 sax of Class H 8/2% calcium chloride.
- Circulated approximately 150 sax to pit. Plug down @ 3:15 P.M. on 11-9-70
- Waited on cement for 17 hrs and applied pressure to casing at 1000# for 30 minutes. There was no pressure drop.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John H. Hendrix TITLE Owner-Operator DATE 11/17/70
APPROVED BY John H. Hendrix TITLE Owner DATE 11/17/70
CONDITIONS OF APPROVAL, IF ANY: