

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input type="checkbox"/>
1. <b>OIL WELL</b> <input checked="" type="checkbox"/> <b>GAS WELL</b> <input type="checkbox"/> <b>OTHER</b> <input type="checkbox"/>		5. State Oil & Gas Lease No.
2. Name of Operator <b>John H. Hendrix</b>		7. Unit Agreement Name
3. Address of Operator <b>316 Central Bldg., Midland, Texas 79701</b>		8. Farm or Lease Name <b>Cossatot</b>
4. Location of Well UNIT LETTER <b>G</b> <b>2310</b> FEET FROM THE <b>North</b> LINE AND <b>2310</b> FEET FROM <b>East</b> <b>12</b> TOWNSHIP <b>22S</b> RANGE <b>37E</b> NMPM.		9. Well No. <b>1</b>
15. Elevation (Show whether DF, RT, GR, etc.)		10. Field and Pool, or Wildcat <b>Wants Abo &amp; Drinkard</b>
12. County <b>Lea</b>		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded @ 6:00 P.M. on June 15, 1971.
- Drilled 12 1/2" hole to 1270'.
- Run 10 jts. of new 2 1/2" J-55 and 26 jts. of new 20# M-46 8 5/8" surface casing (1232') set at 1246'.
- Cemented w/550 sacks Class H cement containing 2% calcium chloride.
- Circulated approximately 10 sax to pit. Plug down @ 1:15 A.M. on 6/17/71.
- Waited on cement for 18 hours. Applied pressure to casing at 1000# for 30 minutes. There was no pressure drop. Tested o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>John H. Hendrix</u>	TITLE <u>Owner-Operator</u>	DATE <u>6/17/71</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>SUPERVISOR DISTRICT 1</u>	DATE <u>JUN 21 1971</u>
CONDITIONS OF APPROVAL, IF ANY:		

