

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-934	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Wood, McShane & Thams-692, Ltd.		New Mexico "M" State
3. Address of Operator		9. Well No.
P. O. Box 968, Monahans, Texas 79756		75
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>M</u> , <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>1305</u> FEET FROM		
THE <u>West</u> LINE, SECTION <u>20</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3376' (GL)		Lea

16.

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 601' (18 jts.) 5½" 15.5# J-55, 3246' (121 Jts.) 5½" 14# J-55 casing with Lynes 5½" 17# External Csg. Packer set at 3726' (GL), a Lynes 5½" 15.5# Csg. Packer set at 3684'. Landed 5½" csg. at 3264' (GL). Cemented w/165 Sx. Class "C" w/ 1/4# Floseal and 120 Sx. Chem Comp. POB 8:00 AM 12-29-71. Top of cement at 2450' (Calculated). Tested casing with 2500 psi for 30 minutes, no pressure drop. WOC 8 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED B. D. Myrdick TITLE Petroleum Engineer DATE 1-10-72

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 12 1970

OIL CONSERVATION COMM.  
HOUSTON, TEXAS