

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
ESTORIL PRODUCING CORPORATION

3. ADDRESS OF OPERATOR
11th floor, Vaughn Bldg.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 1830' FWL of Sec.
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: 22

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Perforated

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐
☒

5. LEASE
NM 203402659 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
CURRY FEDERAL

9. WELL NO.
TWO

10. FIELD OR WILDCAT NAME (UNDESIG.
ANTELOPE RIDGE-MORROW GAS)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 22, T23S, R34E

12. COUNTY OR PARISH LEA 13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3476' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-25-82 Ran Cast Iron Bridge Plug, set @ 6840', capped w/ 20' cmt w/ dump bailer.

9-28-82 RU Western Acid Equip, spotted 500 gal of 7.5% NeFe acid, RU Zone WL Serv, perforated 7 5/8" csg from 6140'-6160', 1 shot per foot, perforated w/ 1000 lbs pressure applied to csg, broke dwn perfs & pumped spot acid away @ 2 bbls per min.

9-29-82 RU Zone WL Serv, ran Radioactive Tracer Survey across perforations from 6140'-6160', slight channeling up hole to 6130', & dwn hole to 6170'.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kris A. Aeteph TITLE Prod. Clerk DATE 10-8-82

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

SEP 20 1982

ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED

OCT 12 1982

OIL & GAS
DEPARTMENT OF THE INTERIOR
ROSWELL, NEW MEXICO