

UNITED STATES P. O. BOX 1980
HOBBS, NEW MEXICO
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
ESTORIL PRODUCING CORPORATION

3. ADDRESS OF OPERATOR
11th floor, Vaughn Bldg.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 1830' FWL of Sec.
AT TOP PROD. INTERVAL: 22
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input checked="" type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)		

5. LEASE
NM 0552659 A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
CURRY FEDERAL

9. WELL NO.
TWO

10. FIELD OR WILDCAT NAME (UNDESIG. GAS)
ANTELOPE RIDGE-MORROW

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 22, T23S, R34E

12. COUNTY OR PARISH
LEA

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3476' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-8-82 Ran 7 5/8" Cast Iron Bridge Plug, set Bridge Plug @ 7110', capped w/ 20' cement, new plug back total depth: 7090', perforated 7 5/8" casing w/ 1 shot per foot from 7040' to 7080'.

9-9-82 Acidized perforations 7040'-7080' w/ 3000 gallons of 7.5% NeFe acid & 60 ball sealers.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kris D. Bartosh TITLE Clerk DATE 8-13-82

(This space for Federal or State office use)

APPROVED BY _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY, _____
ACCEPTED FOR RECORD
SEP 29 1983

*See Instructions on Reverse Side

RECEIVED
SEP 16 1982

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

RECEIVED

OCT 3 1983

O.C.D.
HOBBS OFFICE