i. m. vil Cons. Commission

Form Approved. Budget Bureau No. 42-R1424

P. O. BOX 1980

HOBBS, NEW MEXICO NEW 2605 52659 A

_	

0111112		110000		
DEPARTMENT	OF	THE	INTERIOR	
GEOLOG	ICAI	SUF	RVEY	

				_
7.	UNIT	AGREEMENT	NAME	

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY	NOTICES	AND	REPORTS	ON	WELL5
(Do not use this fo reservoir, Use Form	rm for proposals	to drill o	or to deepen or p als.)	lug bac	k to a different
reservoir, use roini	3 35. 6 .6. 5.				

8. FARM OR LEASE NAME

1. oil \square other well well 2. NAME OF OPERATOR

CURRY FEDERAL 9. WELL NO. TWO

ESTORIL PRODUCING CORPORATION

(UNDESIG. 10. FIELD OR WILDCAT NAME ANTELOPE RIDGE-MORROW

3. ADDRESS OF OPERATOR

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

11th floor, Vaughn Bldg. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17

SEC. 22, T23S, R34E 12. COUNTY OR PARISH 13. STATE LEA NM

AT SURFACE: 660' FSL & 1830' FWL of Sec. AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

14. API NO.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

15. ELEVATIONS (SHOW DF, KDB, AND WD) 3476' GL

SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON*

(other) PROGRESS REPORT

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

RU CRC WL Serv. Ran acoustical free pipe log to find top of cmt. 8-5-82 Top @ 9910'. RD WL unit.

Tan GR & CN Log form 1100-9900'. RU WL log unit. 8-9-82

PU 5-1/2" CIBP. WIH & set CIBP RU Zone WL SERV. MI & RU PU. 8-10-82 @ 10,880'. Capped w/20' cmt,29New PBTD 10,860'. Perf. 5-1/2" csg.w/1 SPF as follows: 10,269-36', 10648-56', 10668-88', 10,698-758' = 95 holes. RD WL unit. PU 5-1/2" pkr. on 2-7/8" tbq.

> _ Set @ ____ Ft. Subsurface Safety Valve: Manu. and Type 18. I hereby certify/that the foregoing is true and correct Millia (TITLE Prod. Clerk DATE _ SIGNED 1

ACCEPTED FOR RECORDITHIS space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

DATE

OCT 1 4 1982

U.S. GEOLOGICAL SURVEY See Instructions on Reverse Side ROSWELL, NEW MEXICO

> MINERALO CLORAL, CL. .. ROSALLL, HEW MEXILO