

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

COPY TO O.C.C.

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

USA NM-0552659-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Superior-Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Antelope Ridge Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 22, T-23-S, R-34-W

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

1.

OIL
WELL ☐GAS
WELL ☐

OTHER Dry hole

2. NAME OF OPERATOR

Patrick Petroleum Corporation

3. ADDRESS OF OPERATOR

219 Mid-America Bldg., Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' from south line, 1830' from west line

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3746 Gr.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Total Depth 13,500'. Plug and abandon as follows:*

200 sack plug 13,500' - 12,458'

25 sack plug 11,977' - 11,877'

Cut 7 5/8" casing and pull from 4800'. Set 100 foot cement plug,
50 feet below and 50 feet above cut.Set 100 foot cement plug, 50 feet below and 50 feet above, base
of salt at log point of 4700'.Set 100 foot cement plug, 50 feet below and 50 feet above top of
Rustler Anhydrite at log point 882'.

Set 50 foot plug in top of 10 3/4". Set monument.

*Verbal approval received from Mr. Jack Gordon on 3/17/72.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

3/19/72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAR 21 1972

*See Instructions on Reverse Side

J L GORDON
ACTING DISTRICT ENGINEER

Instructions


General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

847-485



RECEIVED

MAY 20 1964

OIL CONSERVATION BOARD
HOUSTON, TEXAS