

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-934	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Wood, McShane & Thams 692, LTD		New Mexico "M" State
3. Address of Operator		9. Well No.
P. O. Box 968 Monahans, TX 79756		64
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>L</u> <u>2620</u> FEET FROM THE <u>South</u> LINE AND <u>20</u> FEET FROM		Langlie Mattix
THE <u>West</u> LINE, SECTION <u>29</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3386' (GR)		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 597' (18 jts.) 5 1/2" 15.5# J-55 and 3131' (97 jts.) 5 1/2" 14# J-55 casing and landed at 3727' (GL). Cemented with 275 sx. Class C w/4% gel and 1/4# floseal/sk. & 120 sx Chem Comp w/10# sd./sk. POB 7:30 PM, 7-21-72. Top of cement at 1800' (calculated). Tested casing with 2500 psi. for 30 minutes; no drop in pressure. WOC 8 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>8-17-72</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>SUPERVISOR DISTRICT</u>	DATE <u>AUG 28 1972</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

AUG 27 1972

OIL CONSERVATION COMM.
WOLFE, N.Y.

500-100