

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	1118'	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	1210'	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	2373'	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	2517'	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	2775'	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	3339'	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	3662'	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	3862'	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	5047'	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____		T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	5513'	T. Gr. Wash _____	7186'	T. Morrison _____
T. Tubb _____	5962'	T. Granite _____	7412'	T. Todilto _____
T. Drinkard _____	6255'	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____		T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____		T. _____	T. Chinle _____	T. _____
T. Penn. _____		T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____		T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1118	1118	Redbeds & Sand				
1118	1210	92	Anhydrite				
1210	2373	1163	Salt				
2373	2517	144	Dolomite				
2517	2775	258	Sand, Shale & Dolomite				
2775	3339	564	Sand, Shale & Dolomite				
3339	3662	323	Sand, Shale & Dolomite				
3662	3862	200	Dolomite & Anhydrite				
3862	5047	1185	Dolomite & Anhydrite & Shale				
5047	5513	466	Dolomite & Anhydrite				
5513	5962	449	Dolomite & Anhydrite				
5962	6255	293	Sand & Dolomite				
6255	7186	931	Shale, Dolomite & Anhydrite				
7186	7412	226	Quartz Sand, Shale & Dolo.				
7412	7428	16	Granite				