

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Phillips Petroleum Company		8. Farm or Lease Name Sims
3. Address of Operator Room 711, Phillips Building, Odessa, Texas 79761		9. Well No. 7
4. Location of Well UNIT LETTER C 380 FEET FROM THE north LINE AND 2310 FEET FROM THE west LINE, SECTION 24 TOWNSHIP 22-S RANGE 37-E N.M.P.M.		10. Field and Pool, or Wildcat East Brunson Granite Wash
15. Elevation (Show whether DF, RT, GR, etc.) 3326' Gr.		12. County Lea



Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Leatherwood Drilling Company spudded 11" hole 4:30 P.M., 3-17-73. Drilled to 1162'. Set 36 jts. (1161') 8-5/8" O.D., 24#, K-55, ST&C A cond. csg. at 1161'. Howco cemented w/200 sx Trinity LW cmt. w/10% DD + 10% salt followed by 200 sx Class H cmt. w/2% CaCl₂. Plug to 1129'. Max press 300#. Circ. 50 sx. Job completed 5:30 A.M., 5-19-73. WOC 18 hrs., tested csg. to 1500# for 30 min., O.K. WIH w/7-7/8" bit, drld. cmt. 1129-61', started drilling ahead at 1162' on 3-20-73.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	W. J. Mueller	TITLE Senior Reservoir Engineer	DATE 3-20-73
APPROVED BY 		TITLE OIL & GAS INSPECTOR	DATE
CONDITIONS OF APPROVAL, IF ANY:			