

WELL DATA
FOR
SUBSURFACE DISPOSAL

- (1) Name and Number of Disposal Well: AGUA, INC. Blinebry-Drinkard Salt
Water Disposal Well No. C-2
Location of Disposal Well: 660' FNL & 2305' FWL of 2-22-37, Lea
County, New Mexico
Permit Number: NMOCC Order No. R-4495
Ownership of surface: State of New Mexico
Ownership of minerals: Exxon Co., U. S. A.

- (2) Injection formation and interval: San Andres 4400-4950'

- (3) Disposal Well data:

	<u>Surface Casing</u>	<u>Intermediate Csg.</u>	<u>Long Casing</u>
<u>Size</u>	9-5/8"	None	7"
<u>Weight</u>	32#	None	20#
<u>Grade</u>	H-40	None	J-55
<u>Depth set</u>	312'	None	4400'
<u>Type cement & additives</u>	Class "H" w/ 2% CaCl	None	Class "C" w/ 2% CaCl
<u>Amount of cement</u>	175 sx	None	175 sx
<u>Top of cement</u>	Circ. to surface	None	Calc. @ 3400'

- (4) Total Depth & Plug-back TD: TD 4950'

- (5) Completion Method:

Tubing Size & Type: 5-1/2", 14#, K-55, R-2(internally plastic-coated)
Packer Type: Brown Type DL
Packer Depth: 4362'
Anticipated Injection Pressure: Vacuum
Fluid Additives in Casing-Tubing Annulus: Oil

- (6) Plans for monitoring the disposal well to assure that injection is confined to the inection interval and measures to be taken should it be necessary to shut in an individual disposal well:
1. Periodic temperature and/or radioactive tracer surveys will be run down the bore hole to monitor the exit of waste fluids into the subsurface injection interval.
 2. Waste fluids handled by the Disposal System can be diverted, pumped or trucked to various Disposal Wells in the System.
 3. Emergency pits at each Disposal Well in the System.