

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input type="checkbox"/> OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator Atlantic Richfield Company		8. Farm or Lease Name Annie L. Christmas
3. Address of Operator P.O. Box 1978, Roswell, New Mexico 88201		9. Well No. 4
4. Location of Well UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 17 TOWNSHIP 22-S RANGE 37-E NMPM.		10. Field and Pool, or Wildcat Blinebry/Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) To be reported		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drld 8-3/4" hole to 4450' and lost complete circulation returns. In 7 days pumped in 3000 bbls of mud and 1050 sx of cement in 10 stages and could not regain returns. Dry drilled 8-3/4" hole to 5453'. With verbal approval of J. W. Runyan, NMOCC, ran 174 jts of 7" 20# & 23# J-55 & N-80 casing, float shoe and float collar = 5440.43'. Set at 5452.63' RKB. Cemented 7" w/225 sx Halco Light cement followed by 150 sx Class C neat cement. PD w/water at 4:15 PM 6/2/73. TOC @ 4250' by temperature survey. After 36 hrs WOC tested 7" casing to 1500# for 30 min. Held OK. Resumed drilling - 6 1/4" hole. Will run and cement a 4 1/2" 10.5# K-55 liner from about 5350' to T.D.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *A. D. Sletcher* TITLE Dist. Drlg. Supervisor DATE 6/8/73

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: