



OFFICE PHONE 684-8861
RESIDENCE PHONE 684-6818

JOHN H. HENDRIX
OIL PRODUCER
403 WALL TOWERS WEST
MIDLAND, TEXAS 79701

DIAGRAMMATIC SKETCH
Cossatot "J" No. 1
990' FNL & 2310' FEL Section 24
T-22-S, R-37-E

Wantz Granite Wash Zone

Drinkard Zone

Cement top behind 5 1/2" production casing @ 3750' by Temperature Survey.

8 5/8" 24# Surface Casing set @ 1165' and cemented w/450 sacks. Cement circulated.

Granite Wash Tubing

Case I: If Drinkard GOR is over 100,000, 2 3/8" J-55 Granite Wash tubing set @ 7400'.

Case II: If Drinkard is an oil well, 2 1/16" N-80 IJ Granite Wash tubing set @ 7400'.

Drinkard Zone

Proposed Perforations 6263'-7050'

Case I: If Drinkard GOR is over 100,000, Drinkard will be produced up casing-tubing annulus.

Case II: If Drinkard is an oil well, 2 1/16" N-80 IJ Drinkard tubing set @ 6950'.

Baker Model "D" Production Packer set @ 7148'.

Wantz Granite Wash Zone

Perforations 7214'-7423'.
(18 holes).

5 1/2" 17# Production casing set @ 7455' and cemented w/650 sacks.

PBTD 7434'.
Total depth 7440'.

