Form 9-331 (May 1963)		D STATES OF THE INTERI	* SUBMIT IN TRIPI/ (Other instructions verse side)	Te Form approved. Budget Eureau No. 42-R1424. O. LEASE DESIGNATION AND SERIAL NO.
	GEOLOGICAL SURVEY Roswell, New Mexico			co LC 064427
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR FERMIT-" for such proposals.)				6. IF INDIAN, ALLOTTEE OR TRIBE NAME
J. OIL GAS OTHER				7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Sohio Petroleum Company				8. FARM OR LEASE NAME Elliott B-12-2
3. ADDRESS OF OPERATOR P O Box 3000, Midland, Texas 79702				9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface				10. FIELD AND FOOL, OB WILDCAT Drinkard + Wantz Granite
	NL, 660' FWL, Se	Unit E Sec. 12, T22S,R37E		
14. PERMIT NO.		ELEVATIONS (Show whether DF, 3343' G.L.	RT, GR, etc.)	12. COUNTY OF PARISH 13. STATE Lea New Mexico
16.	Check Approp	riate Box To Indicate N	ature of Notice, Repo	그는 것 같은 것 같은 것 같아. 이 겠 ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ? ?
	NOTICE OF INTENTION ?	ro :		SUBSEQUENT REPORT OF:
TEST WATER SHI	PULL O	DR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT		PLE COMPLETE	FRACTURE TREATMEN	
SHOOT OR ACIDIZ			SHOOTING OR ACIDIZ	ING ABANDONMENT*
LEPAIR WELL     X     CHANGE PLANS       (Other)     (Other)   (Other) (Other)				
This is a 2-1/16th at 7343' with ceme unknown the 5-1/1 1300', an	A ff well is directionally a dual Drinkard tubing. Both zo & cemented with ent circulated f source of press 2" will be press nd the 8-5/8" an	drilled, give subsurface locat and Granite Wash ones are isolated a 675 sacks of cent to surface. The ure buildup. The sure tested to 10	ions and measured and tru well producing by packers. Th ment. The 8-5/8" 8-5/8" ruptured two strings of 00 psi. It will mented with 285	through parallel strings of e vertical depths for all markers and zones peru- through parallel strings of e 5-1/2" long string is set surface pipe is set at 128", 128 at the surface due to an tubing will be pulled, and then be perforated at sacks of Class C cement. This tothe surface.
	cipated starting vailability.	g date is Septemb	er 29, 1980. Ho	wever, it is contingent
<del>X-Rec</del>	<del>. 15 5 1, 6 4 7</del>	<del>6.7 = x</del> .		Funder a sur propert of the structure structure structure structure of the structure structure structure of the structure structure structure of the structure structure structure of the structure structu
18. I hereby certify SIGNED	that the foregoing is true		District Enginee	r DATE 9/25/80
(This space for )	Pederal or State office use	)	<u>, and an </u>	APPROVED
	APPROVAL IF ANY	TITLE		DATE
CONDITIONS OF	" APPROVAL, IF ANY:			SEP 3 0 1980
		*See Instructions	on Reverse Side	DISTRICT SUPERVISOR

t