

COPIES RECEIVED	
TRIBUTION	
FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-934	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Wood, McShane & Thams - 692, Limited		New Mexico M State
3. Address of Operator		9. Well No.
P. O. Box 968, Monahans, Texas 79756		76
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>0</u> <u>100</u> FEET FROM THE <u>South</u> LINE AND <u>1400</u> FEET FROM		Langlie Mattix
THE <u>East</u> LINE, SECTION <u>30</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
3393' (GL)		Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 3809' (118 Jts) 5-1/2" OD 14 and 15.5# J-55 8Rd. casing and set at 3809' (GL). Cemented with 175 Sx. Poz-Mix w/8% gel and 200 Sx. Class H w/18% salt and 5# Gilsonite/sack. POB 4:00 AM, 9-7-73. Top of cement at 2500' (calculated) Tested casing at 2000 psi for 30 minutes; no drop in pressure. WOC 24 hours.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNED <u>R. D. M. Smith</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>9-18-73</u>	
APPROVED BY <u>John W. Ramsey</u>	TITLE <u></u>	DATE <u>9-21-1973</u>	
CONDITIONS OF APPROVAL, IF ANY:			