

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032573 (6)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

CONTINENTAL OIL COMPANY

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1980' FSL & 1780' FEL of Sec. 6

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,447' GR

12. COUNTY OR PARISH

13. STATE

Lea

H. Mex.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETE

☐

SHOOT OR ACIDIZE

☐

ABANDON*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐

REPAIRING WELL

☐

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONMENT*

☐

(Other) P.B. 4 Set Prod. String

☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was P.B. from the Ellenburger, TD 9,466' to PBD 6,750' by setting a 50 inch Class 'C' cement plug from 9,175' to 9,250'. A 75 inch Class 'C' cement plug from 8,785' to 8,650'; and a 50 inch Class 'C' cement plug from 6,885' to 6,750'. Mud was placed between plugs.

The Ellenburger was cemented by DST, the McKee and also were cemented by log analysis.

Set 7" 23" & 26" casing at 6,777'. Cemented with 300 sacks Class 'C' cement. P.B.R. at 6,720', T.O.C. by survey at 5,110'.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Division Office Manager

DATE 2-14-74

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

USGS-S, NMVU-4, File

*See Instructions on Reverse Side