

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032573 (62)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR CONTINENTAL OIL COMPANY	8. FARM OR LEASE NAME Ellenburger
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, N.M. 88240	9. WELL NO. 6
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1780' FEL of Sec. 6	10. FIELD AND POOL, OR WILDCAT Ellenburger - Pritchard
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3,447' GR
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 6, T-22.5, R-37E
	12. COUNTY OR PARISH Lea
	13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☒ Plug back from EllenburgerPULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

It is proposed to plug this drilling well back from the Ellenburger ls. the following procedure: set a 50 sack cement plug from 9,175'-9,050' (Ellenburger); set a 75 sack cement plug from 8,735'-8,650' (Mesa); set a 50 sack cement plug from 6,885'-6,740' (Acho). mud will be placed between plugs. 7" 23 1/2 K-55 OM H-80 and 7" 26" K-55 casing will be set at ± 6,745' and cemented with 300 sacks Class "C" cement.

On DST #1 (QH) 9,100'-9,253', rec. 1100' slightly gas cut mud and 700' water in drill pipe; no gas to surface.

Verbal approval was secured from Mr. Arthur Brown to plug back this well on 2-11-74.

18. I hereby certify that the foregoing is true and correct

SIGNED

Arthur R. Brown

TITLE

Division Office Manager

DATE

2-11-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

FEB 13 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

USGS-S, NMFO-4, File

*See Instructions on Reverse Side