

| | |
|-----------------|--|
| COPIES RECEIVED | |
| DISTRIBUTION | |
| DATE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| | | |
|----------------------------|--------------------------------|---|
| 5a. Indicate Type of Lease | State <input type="checkbox"/> | Fee <input checked="" type="checkbox"/> |
|----------------------------|--------------------------------|---|

5. State Oil & Gas Lease No.

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

| | |
|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 7. Unit Agreement Name |
| 2. Name of Operator Gulf Oil Corporation | 8. Farm or Lease Name F. J. Danglade |
| 3. Address of Operator Box 670, Hobbs, New Mexico 88240 | 9. Well No. 2 |
| 4. Location of Well UNIT LETTER <u>N</u> <u>770</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>13</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> NMPM. | 10. Field and Pool, or Wildcat Granite Wash |
| 15. Elevation (Show whether DF, RT, GR, etc.) | 12. County Lea |

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Capitan Drilling Company spudded 12-1/4" surface hole at 4:30 PM, December 21, 1973. Drilled to 1198'. Ran 28 joints and 1 cut joint, 1183' of 9-5/8" OD 32.30# H-40 ST&C casing set and cemented at 1196' with 300 sacks of Class C with 4% gel and 200 sacks of Class C with 2% Ca C12. Cement circulated.

WOC 18 hours. Tested casing with 1500#, 30 minutes, OK. Started drilling 8-3/4" hole at 1198'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. R. Korychewski TITLE Senior Engineer DATE December 27, 1973

APPROVED BY _____ TITLE _____ DATE 1973

CONDITIONS OF APPROVAL, IF ANY: