

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator <b>Anadarko Production Company</b>	8. Farm or Lease Name <b>E. W. Walden</b>
3. Address of Operator <b>P. O. Box 247, Hobbs, New Mexico 88240</b>	9. Well No. <b>11</b>
4. Location of Well UNIT LETTER <b>M</b> , <b>990</b> FEET FROM THE <b>South</b> LINE AND <b>660'</b> FEET FROM THE <b>West</b> LINE, SECTION <b>15</b> TOWNSHIP <b>22S</b> RANGE <b>37E</b> NMPM.	10. Field and Pool, or Wildcat <b>Penrose-Skelly</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3397' GR 3408' RKB</b>	12. County <b>Lea</b>

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. MIRU W.E.K. Drlg. Company 12-4-73.
2. Spudded 11" hole at 4:00 PM 12-4-73.
3. Drilled 357' of hole.
4. Ran 340' 8-5/8" 24# J-55 Csg. Set at 351'.
5. Cemented with 150 sks of Cl "C" cement with 2% Cacl. plug down at 10:30 PM 12-4-73.
6. S.I.W.O.C. for 18 hrs.
7. Pressure tested surface casing to 1000 psi for 30 minutes without loss of pressure.
8. Drilling ahead with 7-7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Joe D. Ramey</u>	TITLE <u>Area Supervisor</u>	DATE <u>2-6-74</u>
APPROVED BY <u>Joe D. Ramey</u>	TITLE <u>Dist. I, Supv</u>	DATE <u>FEB 8 1974</u>
CONDITIONS OF APPROVAL, IF ANY:		