	State of New Mexico .nergy, Minerals and Natural Resources			Form C-103
Office District I .nergy, Minerals				Revised March 26: 1999
625 N. French Dr., Hobbs, NM 88240		WELL API NO 30-025-24	· ·	
District II 11 South First, Artesia, NM 88210 OIL CONSERVATION DIVISION		5. Indicate Typ		
District III 1220 South St. Francis Dr.		STATE	FEE X	
1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505			Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM				
87505 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Nam				
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A				-
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			SOUTH I	EUNICE UNIT
1. Type of Well:				
Oil Well Gas Well Other INJECTION			0 11/11/1	
2. Name of Operator			8. Well No. 65	
BRECK OPERATING CORP. 3. Address of Operator			9. Pool name o	
P.O. BOX 911, BRECKENRIDGE, TEXAS 76424				7 RIVERS QUEEN, SO
4. Well Location				
			200	at Except to
Unit Letter O: 660 feet from the	SOU	<u>TH</u> line and <u>19</u>	teet from	the <u>EAST</u> line
Section 28 Township 22S	Range	36E NM	PM LEA Co	ounty
10. Elevation (Show)				,
G.R. 3480'				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO:	<i>ي</i> د	1	SEQUENT <u>R</u>	
PERFORM REMEDIAL WORK PLUG AND ABANDON	1 729	REMEDIAL WOR	K 🗀	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS		COMMENCE DRI	LLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING MULTIPLE		CASING TEST AN	ND	ABANDONNENT
COMPLETION		CEMENT JOB		
OTHER:		OTHER:		
12. Describe proposed or completed operations. (Clearly s	tate all per	tinent details, and g	ive pertinent date	es, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion				
or recompilation.				
1. Circulate hole with mud				
2. Spot 50 sacks cement 2700'-3450'. Tag	TUE OC		F DE LIOTIEIRO A	
 Spot 25 sacks cement 1225'-1500'. Perf & tag. THE COMMISSION MUST BE NOTIFIED 24 Spt 40 sacks cement Surface – 600'. HOURS PRIOR TO THE BEGINNING OF 				
 4. Spt 40 sacks cement Surface – 600'. 5. Install dryhole marker and clean location. HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 				
J. Instant dryffold marret and established	TO BE	APPROVED,		
		**		
			<u>*</u>	
			*	
I I I I I I I I I I I I I I I I I I I				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Linda Venekamp	_TITLE_	PRODUCTION		DATE June 28, 2001
Type or print name LINDA VENEKAMP		Telepho	one No. (254) : SIGNED BY KAUTZ LENGINEER	559-3355
(This space for State use)		UNIGINAL	SIGNED AV	
(PETDO: -	. KAUTZ	
APPPROVED BY	_TITLE	LIKULEUN	1 ENGINEED	DATEUL 1 6 2002
Conditions of approval, if any:				