

COPIES RECEIVED		
TRIBUTION		
FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
3. Address of Operator		9. Well No.
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>K</u> , <u>1330</u> FEET FROM THE <u>South</u> LINE AND <u>1330</u> FEET FROM		<u>Langlie-Mattix</u>
THE <u>West</u> LINE, SECTION <u>33</u> TOWNSHIP <u>22S</u> RANGE <u>37E</u> NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
<u>3350' GR</u>		<u>Lea</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		OTHER <u>Spud and set 8-5/8" OD casing</u> <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) Spudded 11" hole at 1:30 p.m. 8-15-74.
- 2) Drilled to 495'.
- 3) Set 12 joints (497') 8-5/8" OD casing at 480'.
- 4) Cemented with 170 sacks Trinity lightweight cement, 2% CaCl, 1/4# flocele and 80 sacks Class "C" cement, 2% CaCl. Cement circulated to surface. WOC 20-1/4 hours.
- 5) Tested 8-5/8" OD casing to 1000# for 30 minutes, held okay.
- 6) Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED (Signed) J. R. Avent J. R. Avent TITLE Dist. Admin. Coord. DATE 8-20-74

APPROVED BY Orig. Signed by Joe D. Ramsey TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: