

COPIES RECEIVED		
DISTRIBUTION		
NTA FE		
E		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator SOHIO PETROLEUM COMPANY		8. Farm or Lease Name Hinton
3. Address of Operator P. O. Box 3000, Midland, Texas 79701		9. Well No. 14
4. Location of Well UNIT LETTER J , 2169 FEET FROM THE South LINE AND 2169' FEET FROM THE East LINE, SECTION 12 TOWNSHIP 22S RANGE 37E NMPM.		10. Field and Pool, or Wildcat Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3339' G.R.		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilling Contractor: Leatherwood Drilling Company

**Spudded: 7:00 P.M., October 3, 1974. Drld 11" hole to 1251', October 5, 1974.
Ran 31 jts, 8-5/8", 24#, set at 1242' KB. Top jt. is 28#. Cemented with 300 sacks
Incor 4% Gel and 130 sacks Incorpor neat. Cemented to surface. Bump plug @ 800 PSI.**

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *J. H. Walters* **J. H. Walters** TITLE Midland District Superintendent **10/8/74**

APPROVED BY *Joe D. Honey* **Joe D. Honey** TITLE District Supv. DATE 10/7/74

CONDITIONS OF APPROVAL, IF ANY: