

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-24865
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	

7. Lease Name or Unit Agreement Name	Ares State
8. Well No.	2
9. Pool name or Wildcat	Jalmat Tansill Yates 7 Rvrs

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator Clayton W. Williams, Jr., Inc.
3. Address of Operator Six Desta Drive, Suite 3000 Midland, Texas 79705	4. Well Location Unit Letter H : 1980 Feet From The N Line and 660 Feet From The East Line Section 16 Township 23S Range 36E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) GR - 3450'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER: <input type="checkbox"/>
OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/15/93 Set CIBP @ 3500'. Dump 35' of cement on CIBP.

3/17 - Displace hole w/60 bbls 10 PPG gelled brine from CIBP to surface.
3/19/93 Perforate 4-1/2" casing @ 370', 2 SPF. Pump 135 sx Class "C" w/2%
CaCl2 down 4-1/2" casing and up 4-1/2"/8-5/8" annulus. Circulate
10 sx cement to pits. Cut casing 3' below GL and install P & A
marker.

SEE ATTACHED WELLBORE DIAGRAM

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

David Grafe

TITLE

Petroleum Engineer

DATE 3/26/93

TYPE OR PRINT NAME

David Grafe

TELEPHONE NO 682-6324

(This space for State Use)

APPROVED BY

Charles Brown

TITLE

OIL

DATE

APR 20 1993

CONDITIONS OF APPROVAL, IF ANY: