

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM 2386-A

6. If Indian, Allottee or Tribe Name

7. If Unit or C.A. Agreement Designation

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Toco, LLC

3. Address and Telephone No

500 W. Texas, Ste 710, Midland, Texas 79702

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1980' FEL
Sec 20, T23S, R33E

8. Well Name and No.

Brinninstool #1

9. API Well No.

30 025 24893

10. Field and Pool, or Exploratory Area

Brinninstool Cruz Bone Spring

11. County or Parish, State

Lea County, New Mexico

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- Squeeze off existing perforations (11,610' to 11,620') in the depleted 2nd Bone Spring.
- Fish existing Baker Retrieval "D" Pack with tubing stub @ 12,194' and tubing stub and seal assembly in PBR at 12,560'.
- Clear out to below existing lower Morrow perforations at 15,586' to 15,597'.
- Reperforate lower Morrow interval 15,586' to 15,597' with 3-1/8" gun, 4 spf.
- Isolate upper Morrow perforations (15,306' to 15,378') with 5" permanent packer set at 15,450' and frac lower Morrow using Alcofoam.

SEE ATTACHED SCHEMATIC

13. I hereby certify that the foregoing is true and correct

Signed

Title

Date

4/1/96

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

Date

PETROLEUM ENGINEER

4/17/96

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

25/2/2011
Received
Hobbs
JGD

BRINNINSTOOL UNIT NO I

1980' FNL. + 1980' FEL

SECTION 20-T235-R33E

LEA COUNTY, NEW MEXICO



